

| INPUT | |
|-------------------|-------------------------------------|
| Rated power | 800 VA |
| Voltage | 220 / 230 / 240 V |
| Voltage tolerance | 230 V (+20/-25%) |
| Frequency | 50 / 60 Hz with automatic selection |

| OUTPUT and INVERTER OUTPUT | |
|--------------------------------|----------------------|
| Rated power | 800 VA |
| Active power | 480 W |
| Number phases | 1 |
| Wave form on battery | Pseudo Sinusoidal |
| Frequency on battery operation | 50 or 60 Hz (+/- 1%) |

| BATTERIES | |
|-----------------------|--------------------------------------|
| Type | VRLA AGM maintenance-free lead based |
| Typical recharge time | 6-8 h |

| ENVIRONMENTAL | |
|-----------------------|---|
| Color | Black |
| Communication | USB |
| Accessories provided | power cable, user guide |
| Marks | CE; GS/NEMKO on Schuko version |
| Operating temperature | 0 °C - +40 °C |
| Relative humidity | 5-95% non-condensing |
| Output sockets | 6 sockets (Schuko or Italian or French or British) + 2 IEC 320 C13 |
| Standards | European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant |

| DATA | |
|--------------------|---------------|
| Weight | 4.1 kg |
| Dimensions (h w d) | 99x185x313 mm |