iDialog

IDG 1600

INPUT	
Rated power	1600 VA
Voltage	220 / 230 / 240 V
Voltage tolerance	230 V (+20/-25%)
Frequency	50 / 60 Hz with automatic selection

OUTPUT and INVERTER OUTPUT	
Rated power	1600 VA
Active power	960 W
Number phases	1
Wave form on battery	Pseudo Sinusoidal
Frequency on battery operation	50 or 60 Hz (±1%)

BATTERIES	
Type	VRLA AGM maintenance-free lead based
Typical recharge time	6-8 h

ENVIRONMENTAL	
Communication	USB
Accessories provided	2 output power supply cables, user manual
Marks	CE
Operating temperature	0 °C - +40 °C
Relative humidity	5-95% non-condensing
Standards	European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant

DATA	
Weight	6.9 kg
Dimensions (h w d)	270x93x310 mm

© RPS Spa - Member of the Riello Elettronica Group - VAT IT02647040233 - Fully paid-up share capital: € 1.230.278,00 - Business Register Verona: N° REA 252286