

# Master Switch Three-phase MTS 100 3P



| INPUT                      |                                   |
|----------------------------|-----------------------------------|
| Voltage                    | 380 / 400 / 415 V three-phase + N |
| Voltage tolerance          | 180 / 264 (selectable)            |
| Frequency                  | 50 / 60 Hz                        |
| Frequency tolerance        | ±10% (selectable)                 |
| Switched input phases      | 3 (3-pole)                        |
| Distribution compatibility | IT, TT, TNS, TNC                  |

| ENVIRONMENTAL            |                                                                 |
|--------------------------|-----------------------------------------------------------------|
| Color                    | RAL 7024                                                        |
| Protection rating        | IP20                                                            |
| Other compliances        | EN 62310-1 (safety) EN 62310-2 (electro-magnetic compatibility) |
| Noise (at 1 m)           | 55 dBA                                                          |
| Operating temperature    | 0 °C - +40 °C                                                   |
| Storing temperature      | -10 °C up to +50 °C                                             |
| Relative humidity        | 5-95% non-condensing                                            |
| Transport                | Pallet jack                                                     |
| Available transfer modes | Automatic / Manual / Remote                                     |

| DATA               |                 |
|--------------------|-----------------|
| Weight             | 150 kg          |
| Dimensions (h w d) | 1500x685x530 mm |